



**CREME DE LA CREME**

SOLID - SKU #AH-750100  
ENGINEERED - SKU #AH-625100

**WAGNER**

SOLID - SKU #AH-750102  
ENGINEERED - SKU #AH-625102

**COBB**

SOLID - SKU #AH-750103  
ENGINEERED - SKU #AH-625103

SPECIES:	<b>Ash</b>
CUT:	<b>Plain Sawn</b>
GRADE:	<b>Select</b>
FINISH:	<b>Matte Polyurethane</b>
Janka Hardness (ASTM D 1037):	1,320
Flame Spread Class Rating (ASTM E 84):	Class III (C)
Flame Spread Index (ASTM E 84):	100
Smoke Developed Index (ASTM E 84):	100
Standard Millwork:	Tongue & Groove, Endmatched

**STANDARD DIMENSIONS & EDGE DETAIL:**

	Solid	Engineered
Thickness:	3/4"	3/4" (5 mm wear layer)
Width:	5"	5"
Random Lengths:	2'-10'	2'-10'
Edges:	Microbevel	Microbevel

NWFA/NOFMA grading guidelines:

**SELECT GRADE:**

A flooring product with coloration variations produced by differences of natural heartwood and sapwood, along with characters described. The face may contain: unlimited sound sapwood; slight imperfections in milling; a small tight knot every 3'; pin worm holes; burls and a reasonable amount of slightly open checks. Brown streaks should not extend the entire length of a piece. Two flag worm holes to every 8' are permitted. Slight imperfections in face work (torn grain) admitted. An intermittent, brown machine burn across the face not exceeding 1/4" width admitted.

**APPLICATIONS:** reSAWN's ASH products are for INTERIOR applications - walls, ceilings, millwork and flooring (not recommended for exterior applications)

**INSTALLATION GUIDE:**

- Acclimatization is vital to minimize swelling & shrinking
- Visit [reawntimberco.com](http://reawntimberco.com)'s A+D Support page to download Installation Guidelines

	Solid	Engineered
Above-grade	YES	YES
On-grade	YES	YES
Below-grade	<b>NO</b>	YES
Over Radiant Heat	YES	YES

**ACCEPTABLE SUB-FLOORS and INSTALLATION METHODS** - see installation guidelines for additional details and recommended adhesive:

Plywood Sub-floor : Glue-down, Nail-down, Staple-down  
 Concrete Sub-floor: Glue-down

**PACKAGING AND FREIGHT:** All shipments are carefully packaged on 12' long pallets

**SUSTAINABLE ATTRIBUTES:**



All ASH designs are available as FSC-certified upon request.

CERTIFICATION

Available as FSC-Certified  
 MR 5 - Regional Materials (based on project location)  
 MR 7 - Certified wood (as FSC-Certified)

POSSIBLE LEED CREDITS

EQ 4.1 - Low-emitting materials: Adhesives & Sealants (Engineered)  
 EQ 4.4 - Low-emitting materials: Composite Wood & Agrifiber Products (Engineered)

Photo Disclaimer: Project and product photos are meant to be a general guide to product appearance only. Due to our handcrafted process and wood being a product of nature, the color, grain pattern, character and profile will vary between individual boards on a project and will never be an exact match.

Janka Rating from similarly tested products - expected to be close to actual measurements of reSAWN TIMBER co.'s products.

Data from Forest Products Laboratory (FPL) General Technical Report (GTR) 190 - expected to be close to actual measurements of reSAWN TIMBER co.'s products.